Optibrite

Product Code: 2509206
Revised Date: 07/26/2011

Optibrite

Optibrite contains a dye that absorbs ultraviolet light. The product is added to Hubbard-Hall's Metal Guard® 900 series and Metal Guard® 600 series products in order to verify the presence of a protective film, when exposed to ultraviolet light.

Optibrite is added at concentrations from 0.5 oz/gal to 1 oz/gal, depending upon the degree of ultraviolet fluorescence desired.

It is advisable to experiment with small samples prior to adding **Optibrite** to production tanks to optimize the concentration.

PHYSICAL DATA

Specific gravity ..... 1.018 @ approx. 70° F
Percentage of volatility by volume .....N/A
Solubility in water ..... Complete
Boiling point .....>212
pH .....10.0 – 11.0
Appearance and odor .....Clear yellow solution

NOTE: Product should be thoroughly mixed prior to use.

Read and understand OSHA Safety Data Sheet prior to handling or working with this product.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

info@hubbardhall.com
P.O. Box 790 ● Waterbury, CT 06720-0790● Tel: (203) 756-5521 ● Fax: (203) 756-9017
www.hubbardhall.com